


- SPECIFICATIONS:
- *PNEUMATIC ACTUATION
 - *POSITION INDICATOR: 24 VDC OR 120 VAC
 - *KF40 PORT FLANGES
 - *VITON GATE AND BONNET SEAL
 - *VACUUM RANGE: 1 X 10⁻⁹ TORR
 - *LEAK TEST: 1 X 10⁻⁹ STD CC/SEC HE
 - *BAKE TEMPERATURE: 120 °C (248 °F)
 - *SST EXPOSED TO VACUUM
 - *OPENS AND SEALS AGAINST APMOSPHERE

NOTE:
1. DIMENSIONS IN [X.XX] ARE IN mm.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
TLI ENTERPRISES, INC. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
THERMIONICS LABORATORY INC. IS
PROHIBITED.

<div>DIMENSIONS ARE IN INCHES</div> <div>TOLERANCES:</div> <div>FRACTIONAL ± N/A</div> <div>ANGULAR: MACH ± BEND ± .5°</div> <div>ONE PLACE DECIMAL ± .1</div> <div>TWO PLACE DECIMAL ± .01</div> <div>THREE PLACE DECIMAL ± .005</div> <div>SURFACE FINISH 63 R.M.S.</div>		FINISH:		<div></div> <div>thermionics</div> <div>laboratory, inc.</div>		DO NOT SCALE DRAWING		REVISION			
						<div>thermionics laboratory inc.</div> <div>3118 Depot Rd., Hayward Ca. 94545</div>					
		NAME		SIGNATURE		DATE		USED ON		NEXT ASSY.	
DESIGN/ENG.										GEN. USE	
CHK'D											
APPV'D											
MFG											
Q.A						MATERIAL:		DWG NO.		TL-1500-P-KF40	
						WEIGHT:		SCALE:1:2		SHEET 1 OF 1	